

Мощность	обороты на выходе n ₂ (об/мин)	крутящий момент M _{2max} (Hm)	передаточное число i	сервис - фактор sf	тип редуктора	тип двигателя
3000						
0,75	97.0	71	28.88	2.8	VRT022	АИС80А2
	117.4	59	23.85	3.4	VRT022 F	АИС80А2
	139.4	49	20.08	4.1		
	163.7	42	17.10	3.8		
1,1	97	104	28.88	1.9	VRT022	АИС80В2
	117	86	23.85	2.3	VRT022 F	АИС80В2
	139	72	20.08	2.8		
	164	62	17.10	3.3		
	189	53	14.81	3.7		
	212	48	13.21	2.9		
1,5	212	65	13.21	2.5	VRT022	АИС90S2
	232	59	12.05	3.4	VRT022 F	АИС90S2
	282	49	9.93	3.3		
	319	43	8.78	2.8		
	379	36	7.39	3.3		
	514	27	5.45	3.7		
1500						
0,18	25.9	64	54.00	3.1	VRT022	АИС63В4
	30.4	55	46.46	3.7	VRT022 F	АИС63В4
	34.5	48	40.60	4.2		
0,25	25.9	88	54.00	2.3	VRT022	АИС71А4
	30.1	76	46.46	2.6	VRT022 F	АИС71А4
	34.5	66	40.60	3.0		
	39.0	59	35.91	3.4		
	48.5	47	28.88	4.2		
0,37	25.9	131	54.00	1.5	VRT022	АИС71В4
	30.1	113	46.46	1.8	VRT022 F	АИС71В4
	34.5	98	40.60	2.0		
	39.0	87	35.91	2.3		
	48.5	70	28.88	2.9		
	58.7	58	23.85	3.5		
	66.7	51	20.08	3.7		
	81.9	41	17.10	3.9		
0,55	25.9	194	54.00	1.0	VRT022	АИС80А4
	30.1	167	46.46	1.2	VRT022 F	АИС80А4
	34.5	146	40.60	1.4		
	39.0	129	35.91	1.5		
	48.5	104	28.88	1.9		
	58.7	86	23.85	2.3		
	69.7	72	20.08	2.8		
	81.9	62	17.10	2.6		
0,75	94.5	53	14.81	3.7		
	30.1	228	46.46	0.88	VRT022	АИС80В4
	34.5	199	40.60	1.0	VRT022 F	АИС80В4
	39.0	176	35.91	1.1		
	48.5	142	28.88	1.4		
	58.7	117	23.85	1.7		
	69.7	99	20.08	2.0		
	81.9	84	17.10	1.9		
	94.5	73	14.81	2.7		
	106	65	13.21	2.5		
	116.2	59	12.05	3.4		
	141	49	9.93	3.3		
	159	43	8.78	2.8		

Мощность	обороты на выходе n ₂ (об/мин)	крутящий момент M ₂ max (Hm)	передаточное число i	сервис - фактор sf	тип редуктора	тип двигателя
1500						
0,75	189	36	7.39	3.3	VRT022	АИС80В4
	257	27	5.45	3.7	VRT022 F	АИС80В4
1.1	39.0	259	35.91	0.77	VRT022	АИС90S4
	48.5	208	28.88	1.0	VRT022 F	АИС90S4
	58.7	172	23.85	1.2		
	69.7	145	20.08	1.4		
	81.9	123	17.10	1.3		
	94.5	107	14,81	1.9		
	106	95	13.21	1.7		
	116	87	12.05	2.3		
	141	72	9.93	2.2		
	159	63	8.78	1.9		
	189	53	7.39	2.3		
	257	39	5.45	2.5		
	316	32	4.43	3.1		
	383	26	3.66	3.8		
1,5	58.7	234	23.85	0.85	VRT022	АИС90LA4
	69.7	197	20.08	1.0	VRT022 F	АИС90LA4
	81.9	168	17.10	1.0		
	94.5	145	14.81	1.4		
	106	130	13.21	1.2		
	116	118	12.05	1.7		
	141	98	9.93	1.6		
	159	86	8.78	1.4		
	189	73	7.39	1.7		
	257	54	5.45	1.9		
	316	44	4.43	2.3		
	383	36	3.66	2.8		
1000						
0,18	16.7	99	54.00	2.0	VRT022	АИС71А6
	19.4	85	46.46	2.3	VRT022 F	АИС71А6
	22.2	74	40.60	2.7		
	25.1	66	35.91	3.0		
	31.2	53	28.88	3.8		
0,25	16.7	138	54.00	1.5	VRT022	АИС71В6
	19.4	118	46.46	1.7	VRT022 F	АИС71В6
	22.2	103	40.60	1.9		
	25.1	91	35.91	2.2		
	31.2	74	28.88	2.7		
0,37	16.7	204	54.00	1.0	VRT022	АИС80А6
	19.4	175	46.46	1.1	VRT022 F	АИС80А6
	22.2	153	40.60	1.3		
	25.1	135	35.91	1.5		
	31.2	109	28.88	1.8		
0,55	19.4	260	46.46	0.77	VRT022	АИС80В6
	22.2	227	40.60	0.88	VRT022 F	АИС80В6
	25.1	201	35.91	1.0		
	31.2	162	28.88	1.2		
	37.7	134	23.85	1.5		
0,75	31.2	221	28.88	0.91	VRT022	АИС90S6
	37.7	182	23.85	1.1	VRT022 F	АИС90S6
	44.8	153	20.08	1.3		

Объем заливаемого масла

Тип редуктора	Объем заливного масла, л.					
	M1	M2	M3	M4	M5	M6
VRT022	0.5	0.7	0.5	0.4	0.4	0.4

Вес редуктора

Тип редуктора	Вес
	Кг
VRT022	6.95