

характеристики мотор-редуктора VRT032

Мощность	обороты на выходе n_2 (об/мин)	крутящий момент M_2 max (Нм)	передаточное число i	сервис - фактор sf	тип редуктора	тип двигателя
3000						
1,1	72.5	139	38.63	2.2	VRT032	АИС80В2
	81.9	123	34.2	2.4	VRT032 F	АИС80В2
	91.6	110	30.57	2.7		
	112	90	24.99	3.3	VRT032	
	132.4	76	21.15	3.7	VRT032 F	
	145.5	69	19.24	4.0		
	153.8	66	18.21	4.3		
1,5	256	54	10.93	3.4	VRT032	АИС90S2
	308	45	9.08	4.0	VRT032 F	АИС90S2
	353	39	7.93	4.6		
2,2	308	65	9.08	2.8	VRT032	АИС90LA2
	353	57	7.93	3.2	VRT032 F	АИС90LA2
	444	45	6.31	4.0		
	511	39	5.48	3.8		
1500						
0,37	27.3	124	51.30	2.4	VRT032	АИС71В4
	31.7	107	44.18	2.8	VRT032 F	АИС71В4
	36.2	94	38.63	3.2		
	40.9	83	34.20	3.6		
0,55	27.3	185	51.30	1.6	VRT032	АИС80А4
	21.7	159	44.18	1.9	VRT032 F	АИС80А4
	36.2	139	38.63	2.2		
	40.9	123	34.20	2.4		
	45.8	110	30.57	2.7		
	56.0	90	24.99	3.3		
0,75	27.3	252	51.30	1.2	VRT032	АИС80В4
	31.7	217	44.18	1.4	VRT032 F	АИС80В4
	36.2	190	38.63	1.6		
	40.9	168	34.20	1.8		
	45.8	150	30.57	2.0		
	56.0	123	24.99	2.4		
	66.2	104	21.15	2.7		
	72.8	94	19.24	3.0		
	76.9	89	18.21	3.1		
	91.5	75	15.30	3.7		
	105	65	13.30	3.8		
	111	62	12.60	4.0		
1,1	27.3	370	51.3	0.81	VRT032	АИС90S4
	31.7	318	44.18	0.94	VRT032 F	АИС90S4
	36.2	278	38.63	1.1		
	40.9	246	34.2	1.2		
	45.8	220	30.57	1.4		
	56	180	24.99	1.7		
	66.2	152	21.15	1.8		
	72.8	139	19.24	2		
	76.9	131	18.21	2.1		
91.5	110	15.3	2.5			

характеристики мотор-редуктора VRT032

Мощность	обороты на выходе n_2 (об/мин)	крутящий момент M_2 max (Нм)	передаточное число i	сервис - фактор sf	тип редуктора	тип двигателя
1500						
1,5	40.9	336	34.20	0.89	VRT032 VRT032 F	AIC90LA4 AIC90LA4
	45.8	300	30.57	1.0		
	56.0	245	24.99	1.2		
	66.2	208	21.15	1.3		
	72.8	189	19.24	1.5		
	76.9	179	18.21	1.6		
	91.5	150	15.30	1.9		
	105	131	13.30	1.9		
	111	124	12.60	2.0		
	128	107	10.93	1.7		
	154	89	9.08	2.0		
	177	78	7.93	2.3		
	222	62	6.31	2.9		
	255	54	5.48	2.8		
	311	44	4.50	3.4		
374	37	3.74	4.1			
2,2	72.8	277	19.24	1.0	VRT032 VRT032 F	AIC100L4 AIC100LA4
	91.5	220	15.30	1.1		
	105	192	13.30	1.3		
	111	182	12.60	1.4		
	128	157	10.93	1.1		
	154	131	9.08	1.4		
	177	114	7.93	1.6		
	222	91	6.31	2.0		
	255	79	5.48	1.9		
	311	65	4.50	2.3		
374	54	3.74	2.8			
3	91,5	301	15.30	0.93	VRT032 VRT032 F	AIC100LB4 AIC100LB4
	105	261	13.30	1.0		
	111	248	12.60	1.0		
	128	215	10.93	0.8		
	154	178	9.08	1.0		
	177	156	7.93	1.2		
	222	124	6.31	1.5		
	255	108	5.48	1.4		
	311	88	4.50	1.7		
	374	73	3.74	2.0		
4	177	208	7.93	0.87	VRT032 VRT032 F	AIC112M4 AIC112M4
	222	165	6.31	1.1		
	255	144	5.48	1.0		
	311	188	4.50	1.3		
	374	98	3.74	1.5		

характеристики мотор-редуктора VRT032

Мощность	обороты на выходе n_2 (об/мин)	крутящий момент M_2 max (Нм)	передаточное число i	сервис - фактор sf	тип редуктора	тип двигателя
1000						
0,37	17.5	193	51.30	1.6	VRT032	АИС80А6
	20.4	167	44.18	1.8	VRT032 F	АИС80А6
	23.3	146	38.63	2.1		
	26.3	129	34.20	2.3		
	29.4	115	30.57	2.6		
0,55	17.5	287	51.30	1.0	VRT032	АИС80В6
	20.4	248	44.18	1.2	VRT032 F	АИС80В6
	23.3	216	38.63	1.4		
	26.3	192	34.20	1.6		
	29.4	171	30.57	1.8		
0,75	17.5	392	51.30	0.77	VRT032	АИС90S6
	20.4	338	44.18	0.89	VRT032 F	АИС90S6
	23.3	295	38.63	1.0		
	26.3	261	34.20	1.1		
	29.4	234	30.57	1.3		
	36.0	191	24.99	1.6		
1,1	36	280	24.99	0.95	VRT032	АИС90L6
	42.7	236	21.15	1.1	VRT032 F	АИС90L6
	47	214	19.24	1.3		
	49.7	203	18.21	1.4		
	59	171	15.3	1.5		
	68	148	13.3	1.7		
	71.8	140	12.6	1.9		
	82.8	122	10.93	2.1		
	99	101	9.08	2.1		
	113	89	7.93	2.0		
	143	71	6.31	2.5		
	164	61	5.48	2.4		
	200	50	4.50	3.0		
	241	42	3.74	3.6		

Объем заливаемого масла

Тип редуктора	Объем заливного масла, л.					
	M1	M2	M3	M4	M5	M6
VRT032	0.8	1.1	0.8	0.6	0.6	0.6

Вес редуктора

Тип редуктора	Вес
	Кг
VRT032	10.25