

характеристики мотор-редуктора VRT042

Мощность	обороты на выходе $n_2$ (об/мин)	крутящий момент $M_2$ max (Hm)	передаточное число $i$	сервис - фактор $sf$	тип редуктора	тип двигателя
<b>3000</b>						
<b>3</b>	308	89	9.08	3.1	VRT042	АИС10L2
	353	78	7.93	3.3	VRT042 F	АИС100L2
	444	62	6.31	4.2		
	511	54	5.48	4.3		
<b>4</b>	308	119	9.08	2.4	VRT042	АИС112M2
	353	104	7.93	2.5	VRT042 F	АИС112M2
	444	83	6.31	3.1		
	511	72	5.48	3.2		
	622	59	4.50	3.9		
<b>1500</b>						
<b>1,1</b>	27.3	370	51.30	1.4	VRT042	АИС90S4
	31.7	318	44.18	1.6	VRT042 F	АИС90S4
	36.2	278	38.63	1.8		
	40.9	246	34.20	1.9		
	45.8	220	30.57	2.2		
	56.0	220	24.99	2.7		
	66.2	152	21.15	2.8		
	72.8	139	19.24	3.0		
	76.9	131	18.21	3.2		
	91.5	110	15.30	3.8		
	105	96	13.30	3.7		
<b>1,5</b>	27.3	504	51.30	1.0	VRT042	АИС90A4
	31.7	434	44.18	1.2	VRT042 F	АИС90A4
	36.2	379	38.63	1.3		
	40.9	336	34.20	1.4		
	45.8	300	30.57	1.6		
	56.0	245	24.99	2.0		
	66.2	208	21.15	2.0		
	72.8	189	19.24	2.2		
	76.9	179	18.21	2.3		
	91.5	150	15.30	2.8		
	105	131	13.30	2.7		
	111	124	12.60	2.8		
	128	107	10.93	2.6		
	154	89	9.08	3.1		
177	78	7.93	3.3			
<b>2,2</b>	40.9	493	34.20	1.0	VRT042	АИС100A4
	45.8	440	30.57	1.1	VRT042 F	АИС100A4
	56.0	360	24.99	1.3		
	67.0	301	21.15	1.4		
	72.8	277	19.24	1.5		
	91.5	220	15.30	1.9		
	105	192	13.30	1.8		
	111	182	12.60	1.9		
	128	157	10.93	1.8		
	154	131	9.08	2.1		
	177	114	7.93	2.3		
	222	91	6.31	2.9		
	255	79	5.48	2.9		
	311	65	4.50	3.5		
374	54	3.74	4.3			

характеристики мотор-редуктора VRT042

Мощность	обороты на выходе $n_2$ (об/мин)	крутящий момент $M_2$ max (Нм)	передаточное число $i$	сервис - фактор $sf$	тип редуктора	тип двигателя
<b>1500</b>						
<b>3</b>	45.8	601	30.57	0.80	VRT042 VRT042 F	AIC100LB4 AIC100LB4
	56.0	491	24.99	1.0		
	67.0	410	21.15	1.0		
	72.8	378	19.24	1.1		
	91.5	301	15.30	1.4		
	105	261	13.30	1.3		
	111	248	12.60	1.4		
	128	215	10.93	1.3		
	154	178	9.08	1.6		
	177	158	7.93	1.7		
	222	124	6.31	2.1		
	255	108	5.48	2.1		
	311	88	4.50	2.6		
374	73	3.73	3.1			
<b>4</b>	105	348	13.30	1.0	VRT042 VRT042 F	AIC112M4 AIC112M4
	111	330	12.60	1.1		
	128	286	10.93	1.0		
	154	238	9.08	1.2		
	177	208	7.93	1.3		
	222	165	6.31	1.6		
	255	144	5.48	1.6		
	311	118	4.50	2.0		
374	98	3.74	2.3			
<b>1000</b>						
<b>0,75</b>	17.5	392	51.30	1.3	VRT042 VRT042 F	AIC90S6 AIC90S6
	20.4	338	44.18	1.5		
	23.3	295	38.63	1.7		
	26.3	261	34.20	1.8		
	29.4	234	30.57	2.1		
<b>1,1</b>	20.5	480	44.18	1.0	VRT042 VRT042 F	AIC90L6 AIC90L6
	23.4	431	38.63	1.2		
	26.4	382	34.20	1.3		
	36.2	278	24.99	1.6		
	42.8	235	21.15	2.0		
47	214	19.24	2.5			
<b>1,5</b>	26.3	523	34.20	0.92	VRT042 VRT042 F	AIC100LA6 AIC100LA6
	29.4	467	30.57	1.0		
	36.0	382	24.99	1.3		
<b>2,2</b>	36.0	560	24.99	0.86	VRT042 VRT042 F	AIC112M6 AIC112M6
	42.7	472	21.15	0.9		
	46.8	431	19.24	1.0		

Объем заливаемого масла

Тип редуктора	Объем заливного масла, л.					
	M1	M2	M3	M4	M5	M6
VRT042	1.2	1.6	1.0	1.0	0.9	0.9

Вес редуктора

Тип редуктора	Вес
	Кг
VRT042	13.3